


PEGASUS

SEGATRICE A NASTRO SEMIAUTOMATICA **PER TAGLI DA 0° A 60° A DESTRA**
SEMIAUTOMATIC BAND SAW MACHINE FOR CUTS FROM 0° TO 60° RIGHT



STANDARD

- ◆ VHZ - Rotazione lama tramite inverter
- ◆ Spazzola motorizzata
- ◆ Riduttore ad ingranaggi (rendimento 95%)
- ◆ Carter arco incernierato
- ◆ Memorizzazione della posizione di inizio e ritorno dell'altezza lama
- ◆ Rotazione arco
- ◆ Fermi di battuta a 0°, 45° e 60°
- ◆ DTI - Dispositivo per taglio interrotto



- ◆ VHZ - Blade rotation by inverter
- ◆ Blade cleaning motorized brush
- ◆ Gear box (efficiency 95%)
- ◆ Hinged head guard
- ◆ Start and return blade height position storing
- ◆ Head rotation
- ◆ Stops at 0°, 45° and 60°
- ◆ DTI - Device for interrupted cut



Ampio piano di appoggio in lato carico con rulli.

Large loading side support with rollers.



Morsa scorrimento rapido.

Fast approach vice.



Scala graduata per lettura angoli.

Graduated scale for angle measure reading.



Ø mm axb mm axb mm axb mm

0°	330	330	330x510	330x510
45° →	330	330	190x360	330x330
60° →	240	160	160x230	160x230

OPTIONAL OPTIONAL

VAT - SENS+SD - LX - DOTM - NB1 BOX - NB2 BOX - TM - RPM1 - QEL SMART - ACP

DOTAZIONI ACCESSORIE ACCESSORY EQUIPMENTS

C2 - CRS-PEG - FM...RSP - FM...RSP DD - RFP1 - RFP2


MOTOR




MOTOR



MOTOR



H2O



OIL

